



# RAVENOL Oldtimer Classic SAE 30 API SB



1L | 1118113-001

5L | 1118113-005

20L | 1118113-020

60L | 1118113-060

**Kategorie:** Oldtimer engine oil (Classic products)

**Artikelnummer:** 1118113

**Viscosity:** 30

**Specification:** API SB

**Oil type:** Mineral

**Application:** Oldtimer

With their unique formulation, **RAVENOL Classic 1 Engine Oils** extend the service life of engines in older vehicles by offering protection against sludge formation and wear and tear. By minimizing friction, fuel consumption is also reduced.

**RAVENOL Oldtimer Classic SAE 30 API SB** is an alloyed single grade engine oil for use in classic vehicles with or without an oil filter. It is manufactured using carefully selected pure mineral raffinates. It provides oxidation stability, it is non-foaming and also has excellent viscosity-temperature characteristics. Thanks to its low setting point, this oil can be used in both low and high temperatures and guarantees perfect lubrication. It is suitable for use in most petrol engines / classic vehicles built before 1951. Using this oil in modern engines can lead to defective performance or cause damage.

## Application Note

**RAVENOL Oldtimer Classic SAE 30 API SB** is designed for use in the engines of vehicles which were built prior to 1951, where the API specification SB is required. Adhere to oil change intervals specified in the manufacturer's instructions.

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	877,0	EN ISO 12185
Colour		gelb	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	11,41	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	103,3	DIN 51562-1
Viscosity Index VI		96	DIN ISO 2909
Pourpoint	°C	-12	DIN ISO 3016
Flashpoint	°C	266	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.