



RAVENOL Super Fuel Economy SFE SAE 5W-20



- 1L | 1111110-001
- 4L | 1111110-004
- 5L | 1111110-005
- 10L | 1111110-010
- 20L | 1111110-020
- 20L | 1111110-B20
- 60L | 1111110-060
- 60L | 1111110-D60
- 208L | 1111110-208
- 208L | 1111110-D28
- 1000L | 1111110-700

Kategorie: Passenger car motor oil

Artikelnummer: 1111110

Viscosity: 5W-20

Specification: ACEA A5/B5, API SN Plus, API SP (RC), ILSAC GF-6A

Oil type: Full synthetic

Approvals: API SN Plus, API SP Resource Conserving, Ford WSS-M2C948-B, ILSAC GF-6A, Jaguar Land Rover STJLR.03.5004

Recommendation: Chrysler MS-6395, Fiat 9.55535-CR1, Ford WSS-M2C925-A, Ford WSS-M2C925-B, Ford WSS-M2C930-A, Ford WSS-M2C930-B, Honda/Acura HTO-06, Mazda, Nissan, Suzuki, Toyota

Application: Passenger car

Technology: Clean Synto®, USVO®

RAVENOL Super Fuel Economy SFE SAE 5W-20 is a PAO (Polyalphaolefin) based, full synthetic low friction motor oil with especially USVO® and proven CleanSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

Due to the USVO® technology we achieve an extremely high viscosity stability. We avoid the disadvantages of polymeric viscosity improvers while taking advantage of them. This improves engine protection, performance, engine cleanliness and oil drain intervals. The USVO® technology makes it possible that the product has no shear losses during the entire change interval and is extremely stable to oxidation. This unique technology helps oil to be lubricated faster, thereby minimizing friction while keeping the engine clean and efficient.

RAVENOL Super Fuel Economy SFE SAE 5W-20 has a high viscosity index because of its formulation with special base oils. The formulation avoids premature fuel ignition LSPI (Low Speed Prevention), thereby avoiding engine damage. Recommended for turbo gasoline engines with direct injection (Turbo-GDI).

Because of a considerable fuel saving **RAVENOL Super Fuel Economy SFE SAE 5W-20** contributes to protect the environment by reducing the emissions.

RAVENOL Super Fuel Economy SFE SAE 5W-20 minimizes friction, wear and fuel consumption with excellent cold start characteristics.

Extended oil change intervals according to the manufacturer's instructions.

Application Note

RAVENOL Super Fuel Economy SFE SAE 5W-20 is an universal fuel-efficient engine oil, a top-quality product for modern passenger cars with gasoline and diesel engines of the latest generation.

Characteristics

- Guaranteed fastest possible lubrication of the engine.
- High fuel economy (FE) effect due to the base oils and additives used. Low volatilization tendency, thereby lower oil consumption.
- Provides protection against sludging, coking, varnish and corrosion even under unfavorable operating conditions.
- No oil-related deposits in combustion chambers in the piston ring zone and on valves.
- Ensures the function of the hydraulic tappets at all temperatures.
- Stable engine oil, no NOx oxidation.
- Good aging behavior, confirmed by the Hot Tube Test.
- Good soot absorption and dispersion.
- Neutral towards sealing materials.
- Protects turbocharger, EPS and engines running with ethanol-containing fuels up to E85.
- Compatibility with exhaust gas after treatment systems.

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	842,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	8,5	DIN 51562-1
Viscosity at 40 °C	mm ² /s	47,2	DIN 51562-1
Viscosity Index VI		160	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	2,9	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	3640	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	9.700	ASTM D4684
Pourpoint	°C	-63	DIN ISO 3016
Noack Volatility	% M/M	8,3	ASTM D5800
Flashpoint	°C	238	DIN EN ISO 2592
tbn	mg KOH/g	8,0	ASTM D2896
Sulphated Ash	%m	0,8	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

06.06.2023